

## S6-EH1P(3-6)K-L-AU

# Solis Single Phase Low Voltage Energy Storage Inverters

### Features:

- Integrated 2 MPPTs for multiple array orientations
- Industry leading 125A/6kW max charge/discharge rating
- Automatic UPS switching
- Supports Peak Shaving Mode
- Pre-made Battery, Meter and CAN cabling to reduce installation time
- Compatible with multiple brands of lithium battery models
- Increased battery protection and operation features to extend battery life

### Models:

S6-EH1P3K-L-AU / S6-EH1P3.6K-L-AU

S6-EH1P4.6K-L-AU / S6-EH1P5K-L-AU

S6-EH1P6K-L-AU



360° View

# DATASHEET

## S6-EH1P(3-6)K-L-AU

Models	3K	3.6K	4.6K	5K	6K
<b>Input DC (PV side)</b>					
Recommended max. PV power	4.8 kW	5.7 kW	7 kW	8 kW	9.6 kW
Max. input voltage	600 V				
Rated voltage	330 V				
Start-up voltage	90 V				
MPPT voltage range	90-520 V				
Max. input current	16 A / 16 A				
Max. short circuit current	24 A / 24 A				
MPPT number/Max. input strings number	2/2				
<b>Battery</b>					
Battery type	Li-ion / Lead-acid				
Battery voltage range	42 - 58 V				
Battery capacity	50 - 2000 Ah				
Max. charge / discharge power	3 kW	3.6 kW	4.6 kW	5 kW	6 kW
Max. charge / discharge current	62.5 A	75 A	100 A	105 A	125 A
Communication	CAN				
<b>Output AC (Grid side)</b>					
Rated output power	3 kW	3.6 kW	4.6 kW	5 kW	6 kW
Max. apparent output power	3 kVA	3.6 kVA	4.6 kVA	5 kVA	6 kVA
Operation phase	1/N/PE				
Rated grid voltage	230 V				
Rated grid frequency	50 Hz				
Rated grid output current	13.0 A	15.7 A	20 A	21.7 A	26.1 A
Max. output current	13.0 A	15.7 A	20 A	21.7 A	26.1 A
Power factor	>0.99 (0.8 leading - 0.8 lagging)				
THDi	3%				
<b>Input AC (Grid side)</b>					
Rated voltage	230 V				
Max. input current	20 A	24.6 A	31.4 A	32 A	40 A
Frequency range	50 Hz				
<b>Output AC (Back-up)</b>					
Rated output power	3 kW	3.6 kW	4.6 kW	5 kW	6 kW
Max. apparent output power	4.2 kVA, 60 sec	5 kVA, 60 sec	6.4 kVA, 60 sec	7 kVA, 60 sec	8 kVA, 60 sec
Back-up switch time	<10 ms				
Rated output voltage	1/N/PE, 230 V				
Rated frequency	50 Hz				
Rated. output current	13.0 A	15.7 A	20 A	21.7A	26.1 A
THDv (@linear load)	3%				
<b>Efficiency</b>					
Max. efficiency	> 97.0%		> 97.5%		
EU efficiency	> 96.2%				
BAT charged by PV Max. efficiency	> 94.9%				
BAT charged/discharged to AC Max. efficiency	> 94.33%/93.51%				
<b>Protection</b>					
DC reverse-polarity protection	Yes				
Ground fault monitoring	Yes				
Integrated AFCI (DC arc-fault circuit protection)	Yes <sup>(1)</sup>				
Protection class/Over voltage category	I/II				
<b>General Data</b>					
Dimensions (W*H*D)	405*480*205 mm				
Weight	20.3 kg		22.4 kg		
Topology	Non-Isolated				
Operating ambient temperature range	-25 ~ +60°C				
Ingress protection	IP66				
Cooling concept	Natural convection				
Max. operation altitude	3000 m				
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA				
Safety/EMC standard	IEC/EN 62109-1/-2, EN 61000-6-1/-2/-3/-4				
<b>Features</b>					
DC connection	MC4 connector				
AC connection	Quick connection plug				
Display	LED + APP				
Communication	RS485, CAN, Optional: Wi-Fi, GPRS, LAN				
Country of manufacture	China				

(1) Activation required.