

## S5-GC(25-50)K-AU

# Solis Three Phase Grid-Tied Inverters

### Efficient

- Max. efficiency 98.8%
- String current up to 16A
- 4 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)
- Wide voltage range and low startup voltage

### Smart

- Support export power control
- Intelligent string monitoring, smart I-V curve scan
- Support RS485, WiFi, GPRS
- Scan to register on SolisCloud, support remote upgrade and control

### Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life
- Intelligent redundant fan-cooling

### Economic

- Supports GPRS/WiFi communication with less wiring and reduced installation costs
- > 130% DC/AC ratio
- Supports high power modules for lower installation costs

### Models:

S5-GC25K-AU / S5-GC30K-AU

S5-GC33K-AU / S5-GC36K-AU

S5-GC40K-AU / S5-GC40K-HV-AU

S5-GC50K-HV-AU



360° View

# DATASHEET

## S5-GC(25-50)K-AU

Models	25K	30K	33K	36K	40K	40K-HV	50K-HV
<b>Input DC</b>							
Recommended max. PV power	33.3 kW	39.9 kW	43.9 kW	47.9 kW	53.2 kW	53.2 kW	66.5 kW
Max. input voltage				1100 V			
Rated voltage				600 V			
Start-up voltage				180 V			
MPPT voltage range				200-1000 V			
Max. input current				4*32 A			
Max. short circuit current				4*40 A			
MPPT number/Max. input strings number				4/8			
<b>Output AC</b>							
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated grid voltage	3/N/PE, 230 V / 400 V					3/PE, 480 V	
Rated grid frequency				50 Hz			
Rated grid current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A	53.0 A	66.2 A
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A	53.0 A	66.2 A
Power factor				>0.99 (0.8 leading - 0.8 lagging)			
THDi				<3%			
<b>Efficiency</b>							
Max. efficiency	98.5%		98.6%	98.7%		98.8%	
EU efficiency	98.1%		98.2%	98.3%		98.4%	
<b>Protection</b>							
DC reverse-polarity protection				Yes			
Short circuit protection				Yes			
Output over current protection				Yes			
Surge protection				DC Type II / AC Type II			
Grid monitoring				Yes			
Anti-islanding protection				Yes			
Temperature protection				Yes			
Strings monitoring				Yes			
I/V Curve scanning				Yes			
Integrated AFCI 2.0				Optional			
Integrated PID recovery				Optional			
Integrated DC switch				Yes (PV2 Switch)			
<b>General Data</b>							
Dimensions (W*H*D)				647*629*252 mm			
Weight	38.2 kg			42.1 kg			
Topology				Transformerless			
Self-consumption (night)				<1 W			
Operating ambient temperature range				-25 ~ +60°C			
Relative humidity				0-100%			
Ingress protection				IP65			
Noise emission (typical)				≤60 dB(A)			
Cooling concept				Intelligent redundant fan-cooling			
Max. operation altitude				4000 m			
Grid connection standard				AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530			
Safety/EMC standard				IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4			
<b>Features</b>							
DC connection				MC4 connector			
AC connection				OT terminal			
Display				LCD			
Communication				RS485, Optional: Wi-Fi, GPRS			
Country of manufacture				China			