

## Solis-(215-255)K-EHV-5G

# Solis Three Phase Grid-Tied Inverters

### Efficient

- 9/12/14 MPPTs, max. efficiency 99.0%
- > 150% DC/AC ratio
- High power tracking density 55MPPT/MW
- Compatible with 550W+ bifacial modules

### Smart

- Night SVG function
- Intelligent string monitoring, smart I-V curve scan
- Remote firmware upgrade with simple operation

### Safe

- IP66
- Built-in PID recovery for better module performance
- Fuse free design, safe and maintenance free
- Globally recognised branded componentry for longer life

### Economic

- Power line communication (PLC) (optional)
- DC side supports "Y" connector

### Models:

Solis-215K-EHV-5G-PLUS

Solis-255K-EHV-5G

Solis-255K-EHV-5G-PLUS



360° View

## DATASHEET

## Solis-(215-255)K-EHV-5G

Models	215K-PLUS	255K	255K-PLUS
<b>Input DC</b>			
Max. input voltage		1500 V	
Rated voltage		1080 V	
Start-up voltage		500 V	
MPPT voltage range		480 - 1500 V	
Max. input current	9 × 30 A	14 × 26 A	12 × 30 A
Max. short circuit current	9 × 50 A	14 × 40 A	12 × 50 A
MPPT number / Max. input strings number	9 / 18	14 / 28	12 / 24
<b>Output AC</b>			
Output power	215 kVA@30°C / 205 kVA@40°C / 195 kVA@50°C	255 kVA@30°C / 235 kVA@40°C / 220 kVA@50°C	
Rated apparent output power	215 kVA	255 kVA	
Rated grid voltage	3/PE, 800 V		
Grid voltage range	640 - 920 V		
Rated grid frequency	50 Hz		
Max. output current	155.2 A	184.0 A	
Power factor	> 0.99 (0.8 leading - 0.8 lagging)		
THDi	< 3%		
<b>Efficiency</b>			
Max. efficiency		99.0%	
EU efficiency	98.8%	98.7%	98.8%
<b>Protection</b>			
DC reverse-polarity protection	Yes		
Short circuit protection	Yes		
Output over current protection	Yes		
Surge protection	DC Type II / AC Type II		
Grid monitoring	Yes		
Anti-islanding protection	Yes		
Temperature protection	Yes		
Strings monitoring	Yes		
I/V Curve scanning	Yes		
Night time SVG function	Yes		
Integrated PID recovery	Yes		
Integrated DC switch	Yes		
<b>General Data</b>			
Dimensions (W × H × D)	1125 × 770 × 384 mm		
Weight	109 kg	113 kg	
Topology	Transformerless		
Self-consumption (night)	< 2 W		
Operating ambient temperature range	-30 ~ +60°C		
Relative humidity	0 - 100%		
Ingress protection	IP66		
Cooling concept	Intelligent fan-cooling		
Max. operation altitude	4000 m		
Grid connection standard	AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530		
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4		
<b>Features</b>			
DC connection	MC4 connector		
AC connection	OT terminal (max. 300 mm <sup>2</sup> )		
Display	LCD		
Communication	RS485, Optional: PLC		
Country of manufacture	China		