

S5-EH1P(3-6)K-L

Solis Single Phase Low Voltage Energy Storage Inverters

Features:

- Max. string input current 15A
- Uninterrupted power supply, 20ms reaction
- Multiple working modes to make maximize self-consumption, increase benefit
- Higher charge-discharge efficiency, improving the economic benefits
- AFCI protection, proactively reduces fire risk
- Fanless design, long lifespan
- Compatible with lithium & lead-acid batteries, increased more choice in different markets
- Intelligent EMS function, improving battery's reliability
- 24-hour fully intelligent energy management, Real-time grasp of PV plant status
- Remotely control & upgrade function, making digital power plant maintenance at your fingertips

Models:

S5-EH1P3K-L / S5-EH1P3.6K-L

S5-EH1P4.6K-L / S5-EH1P5K-L

S5-EH1P6K-L



DATASHEET

S5-EH1P(3-6)K-L

Models	3K	3.6K	4.6K	5K	6K
Input DC (PV side)					
Recommended max. PV power	6 kW	7.2 kW	9.2 kW	10 kW	12 kW
Max. input voltage	600 V				
Rated voltage	330 V				
Start-up voltage	120 V				
MPPT voltage range	90 - 520 V				
Max. input current	15 A / 15 A				
Max. short circuit current	22.5 A / 22.5 A				
MPPT number / Max. input strings number	2 / 2				
Battery					
Battery type	Li-ion / Lead-acid				
Battery voltage range	42 - 58 V				
Battery capacity	50 - 2000 Ah				
Max. charge / discharge power	3 kW				5 kW
Max. charge / discharge current	62.5 A				100 A
Communication	CAN				
Output AC (Back-up)					
Rated output power	3 kW				5 kW
Max. apparent output power	4.5 kVA, 10 s				7 kVA, 10 s
Back-up switch time	< 20 ms				
Rated output voltage	1/N/PE, 230 V				
Rated frequency	50 Hz				
Rated output current	13.5 A				22 A
THDv (@linear load)	< 2%				
Input AC (Grid side)					
Input voltage range	187 - 265 V				
Max. input current	20.5 A	25 A	31.5 A	34.5 A	34.5 A
Frequency range	45 - 55 Hz				
Output AC (Grid side)					
Rated output power	3 kW	3.6 kW	4.6 kW	5 kW	6 kW
Rated apparent output power	3 kVA	3.6 kVA	4.6 kVA	5 kVA	6 kVA
Max. apparent output power	3 kVA	3.6 kVA	4.6 kVA	5 kVA	6 kVA
Operation phase	1/N/PE				
Rated grid voltage	230 V				
Rated grid frequency	50 Hz				
Rated grid output current	15 A	18.5 A	21 A	25 A	30 A
Max. output current	15 A	18.5 A	21 A	25 A	30 A
Inrush current	65 A, 10 us				
Max. output fault current	65 A, 10 us				
Max. output overcurrent protection	16 A	20 A	22 A	26 A	31 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)				
THDi	< 2%				
Efficiency					
Max. efficiency	> 97.1%				
EU efficiency	> 96.5%				
Protection					
DC reverse-polarity protection	Yes				
Short circuit protection	Yes				
Output over current protection	Yes				
Surge protection	DC Type II / AC Type II				
Ground fault monitoring	Yes				
Integrated AFCI	Yes ⁽¹⁾				
Protection class / Over voltage category	I / II (PV), II (battery), III (AC)				
Integrated DC switch	Yes (PV2 Switch)				
General Data					
Dimensions (W × H × D)	333 × 505 × 249 mm				
Weight	17.9 kg				18.1 kg
Topology	Non-isolated				
Operating ambient temperature range	-25 ~ +60°C				
Ingress protection	IP65				
Cooling concept	Natural cooling				
Max. operation altitude	3000 m				
Grid connection standard	G98 or G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA				
Safety / EMC standard	IEC/EN 62109-1/-2, EN 61000-6-2/-3				
Features					
DC connection	MC4 connector				
AC connection	Quick connection plug				
Display	7.0" LCD display				
Communication	RS485, Optional: Wi-Fi, GPRS				
Country of manufacture	China				

(1) Activation required.