



Grid-Tied Inverters

S5-GC(25-50)K-AU

4 MPPT | 32A per MPPT



- Max. efficiency 98.8%
- Intelligent string monitoring, smart I-V curve scan
- 4 MPPT design, suitable for multi-facing roof
- 24-hour load consumption monitoring
- AFCI protection, proactively reduces fire risk
- IP66
- Nighttime PID recovery function (optional)

AUSTRALIA

t: +61 1800928995 e: sales@solisinverters.com.au w: solisinverters.au
+61 3 8555 9516 service@solisinverters.com.au



DATASHEET

S5-GC(25-50)K-AU

Models	25K	30K	33K	36K	40K	40K-HV	50K-HV
Input DC							
Recommended max. PV power	33.3 kW	39.9 kW	43.9 kW	47.9 kW	53.2 kW	53.2 kW	66.5 kW
Max. input voltage				1100 V			
Rated voltage				600 V			
Start-up voltage				180 V			
MPPT voltage range				200 - 1000 V			
Max. input current				4 × 32 A			
Max. short circuit current				4 × 40 A			
MPPT number / Max. input strings number				4 / 8			
Output AC							
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated grid voltage	3/N/PE, 230 V / 400 V					3/PE, 480 V	
Rated grid frequency	50 Hz						
Rated grid current	36.2 A	43.5 A	47.8 A	52.2 A	58.0 A	48.1 A	60.2 A
Max. output current	36.2 A	43.5 A	47.8 A	52.2 A	58.0 A	48.1 A	60.2 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)						
THDi	< 3%						
Efficiency							
Max. efficiency	98.5%		98.6%	98.7%		98.8%	
EU efficiency	98.1%		98.2%	98.3%		98.4%	
Protection							
DC reverse-polarity protection				Yes			
Short circuit protection				Yes			
Output over current protection				Yes			
Surge protection				DC Type II / AC Type II			
Grid monitoring				Yes			
Anti-islanding protection				Yes			
Temperature protection				Yes			
Strings monitoring				Yes			
I/V Curve scanning				Yes			
Multi peak scan				Yes			
Integrated AFCI 2.0				Optional			
Integrated PID recovery				Optional			
Integrated DC switch				Yes (PV2 Switch)			
General Data							
Dimensions (W × H × D)				647 × 629 × 252 mm			
Weight	38.2 kg			42.1 kg			
Topology				Transformerless			
Self-consumption (night)				< 1 W			
Operating ambient temperature range				-25 ~ +60°C			
Relative humidity				0 - 100%			
Ingress protection				IP65			
Noise emission (typical)				≤ 60 dB(A)			
Cooling concept				Intelligent fan-cooling			
Max. operation altitude				4000 m			
Grid connection standard	AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530						
Safety / EMC standard	IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4						
Features							
DC connection				MC4 connector			
AC connection				OT terminal			
Display				LCD			
Communication				RS485, Optional: Wi-Fi, GPRS			
Country of manufacture				China			