

CERTIFICATE OF CONFORMITY / APPROVAL

Authorised marking: TUV-028529-EA

CONTINUATION SHEET 28

(Modification 25)

Classified as:

D.4.5 (f): Enclosed outdoors, exposed to sunlight, mounted in aspecified PCE - for use in PCE enclosure, enclosed outdoor, suitable for installation exposed to sunlight as perAS/NZS 5033.

Switch arrangement: 5 switches arrangement,

5 switches NDG3V-50/4/1/01/M/AS, 4 layers; "+" and "-" in series for 1string, total 10 strings

Installed within Grid-connected PV Inverter

Brand: Solis

Models: Solis-100K-5G-AU, Solis-110K-5G-AU, Solis-125K-HV-5G-AU, S5-GC100K-AU, S5-GC110K-AU, S5-GC125K-HV-AU

Size: 1065mm×567mm×344,5mm (W x H x D)

Enclosure material: AL5052, Wall thickness: 2mm, Volume: 0,20m³

Input: DC-PV2: Ue=1100VDC, Ie=32A

Ui=1500V, Uimp=8kV, Iu=32A, Ithe=32A,

Ithe Solar at 40°C=32A, Ithe Solar at 60°C=24A

Issue Date: 27-10-2025

Expiry Date: 27-10-2030

Signed for and on behalf of TÜV Rheinland Australia Pty Ltd



Rafeeqe Mohamed

© TÜV, TÜEV and TUV are registered trademarks. Utilisation and application requires prior approval.

